

Recommended Core and Drive and Bowl Model	Bowl Description	A Bowl Diameter	B Bowl Height	C Bowl Diameter w/ O. T.	D Track Width	E Discharge Height w/ O. T.		F Centerline Bowl to Discharge	G Outside Track Width	Approx. Bowl Weight (lbs)	Max Part Dimension
						Min	Max				
EB-112-A 10SW12 - OT 10SW14 - OT	Std. Track Pitch	10	6 ^{3/4}	15 ^{1/4}	3/4	3 ^{5/8}	4 ^{5/8}	7 ^{1/8}	2	13	1/2
	Low Track Pitch	10	6 ^{15/16}	--	7/8	3 ^{3/8}	5 ^{1/8}	--	--	13	1/2
EB-132-A 12SW16 - OT 12SW16 - OT	Std. Track Pitch	12	7 ^{15/16}	19 ^{1/8}	1	4	5	9 ^{1/8}	3	19	3/4
	Low Track Pitch	12	7 ^{1/2}	--	1	3 ^{3/4}	5 ^{1/8}	--	--	19	3/4
Legacy (UM-15-S) 12SW16 - OT 12SW16 - OT	Std. Track Pitch	12	7 ^{15/16}	19 ^{1/8}	1	4	5	9 ^{1/8}	3	19	3/4
	Low Track Pitch	12	7 ^{1/2}	--	1	3 ^{3/4}	5 ^{5/8}	--	--	19	3/4
EB-162-A 15SW20 - OT 15SW20 - OT	Std. Track Pitch	15	9 ^{3/8}	23 ^{5/8}	1 ^{1/4}	4 ^{3/4}	6 ^{1/4}	11 ^{1/8}	3 ^{1/2}	29	1 ^{1/2}
	Low Track Pitch	15	9	--	1 ^{1/4}	4 ^{1/8}	6 ^{3/8}	--	--	29	1 ^{1/2}
Legacy (UM-15-L) 15SW20 - OT 15SW20 - OT	Std. Track Pitch	15	9 ^{3/8}	23 ^{5/8}	1 ^{1/4}	4 ^{3/4}	6 ^{1/4}	11 ^{1/8}	3 ^{1/2}	29	1 ^{1/2}
	Low Track Pitch	15	9	--	1 ^{1/4}	4 ^{1/8}	6 ^{3/8}	--	--	29	1 ^{1/2}
EB-192-A 18SW32 - OT 18SW24 - OT	Std. Track Pitch	18	10 ^{3/4}	29	2	5 ^{1/4}	7 ^{1/4}	13 ^{1/8}	4	41	2
	Low Track Pitch	18	10 ^{7/8}	--	1 ^{1/2}	5	7 ^{5/8}	--	--	41	2
EB-222-A 21SW36 - OT 21SW28 - OT	Std. Track Pitch	21	12 ^{3/16}	32 ^{3/4}	2 ^{1/4}	5 ^{1/4}	8 ^{1/4}	14 ^{5/8}	4	59	3
	Low Track Pitch	21	12 ^{1/8}	--	1 ^{3/4}	5 ^{3/8}	8 ^{3/4}	--	--	59	3
EB-252-A 24SW44 - OT 24SW32 - OT	Std. Track Pitch	24	13 ^{3/8}	37 ^{3/4}	2 ^{3/4}	5 ^{3/4}	9	17 ^{1/8}	5	75	4
	Low Track Pitch	24	13 ^{3/4}	--	2	5 ^{7/8}	9 ^{1/2}	--	--	75	4
EB-322-A 30SW48 - OT 30SW40 - OT	Std. Track Pitch	30	16 ^{3/4}	45 ^{3/4}	3	7 ^{3/4}	11 ^{3/8}	21 ^{1/8}	6	109	6
	Low Track Pitch	30	16 ^{5/8}	--	2 ^{1/2}	6 ^{5/8}	11 ^{1/2}	--	--	109	6

EB-372-A

Consult factory for recommended bowl size.

Clockwise and counter-clockwise bowls are available.

